







SPECIFICATIONS

Engine Type	4-Stroke, 4-Valve, DOHC, Liquid-Cooled
Displacement	149 cc
Bore & Stroke	57.3 x 57.8 mm
Compression Ratio	11.3:1
Maximum Power	12.0 kW @ 9,000 rpm
Maximum Torque	13.7 Nm @ 7,000 rpm
Starting System	Electric
Engine Oil Capacity	1.3 L
Fuel System	PGM-FI
Fuel Consumption	41.5 Km/L (HUDC)
Transmission Type	Manual, 6-Speed Constant Mesh
Gear Shift Pattern	1-N-2-3-4-5-6 (Down Up)
Suspension Type (Front)	Inverted Telescopic
Suspension Type (Rear)	Swing Arm with Monoshock (Pro-Link)
Brake Type (Front)	Hydraulic Disc with ABS
Brake Type (Rear)	Hydraulic Disc with ABS
Tire Size & Type (Front)	100/80-17M/C 52P (Tubeless)
Tire Size & Type (Rear)	130/70-17M/C 62P (Tubeless)
Wheel Type	Cast Wheel
Overall Dimensions (L x W x H)	1, 983 X 700 X 1,090 mm
Curb Weight	138 kg
Seat Height	788 mm
Wheelbase	1,310 mm
Ground Clearance	151 mm
Fuel Tank Capacity	12 L
Ignition System	Full Transisterized
Battery Type	12V 5Ah MF-Wet

FEATURES













(2-CHANNEL ABS)

Prevents wheel from locking and better increases stability in sudden stops.

NEW GRAPHICS COLORING

Fire up your ride with its graphic touch up for a sportier look.

GOLD CAST WHEEL COLOR

Make a statement on the road and stand out more than ever.

POWERFUL 149CC.6-SPEED. DOHC LIQUID-COOLED ENGINE

Fireblade-inspired power for a world class racing engine experience. Now equipped with new gold-colored crank-

BANK ANGLE SENSOR

Automatically turns off the engine when bank angle exceeds 60° for your daily safety



ASSIST/SLIPPER CLUTCH

Enables a lighter clutch lever pull for a smooth and accurate ride



INVERTED FRONT SUSPENSION

Stability and handling with a new superior look



LED HEADLIGHT AND FRONT WINKER

Illuminate your way with a sporty headlight design



FULL DIGITAL METER PANEL

AND REAR WINKER more precise information Bright dashing tail lights for maximum safety and style



Winning Red (Honda Tri-Color)

Actual Unit May Vary

Authorized Dealer

USE ONLY:

HONDA

GENUINE PARTS















