









SPECIFICATION

Engine Type	Liquid-Cooled, 4-Valve, 4-Stroke Unicam Single
Displacement	150 cc
Bore X Stroke	66.0 x 43.7 (mm)
Fuel Tank Capacity	4.3 Liters
Clutch Type	Wet, Multiplate Clutch
Transmission Type	5-Speed Manual Transmission
Overall Dimensions (L x W x H)	1,900 X 770 X 1,171 mm
Seat Height	866 mm
Ground Clearance	336 mm
Curb Weight	85 kg
Suspension Type (Front)	37 mm Fully-Adjustable Leading-Axle Inverted Conventional Showa Cartridge. 27.4cm of travel
Suspension Type (Rear)	Pro-Link Fully-Adjustable Showa Single shock. 27.1cm of Travel
Tire Size (Front)	70/100 -19 42M
Tire Size (Rear)	90/100 -16 52M
Wheelbase	1,285 mm
Brake Type (Front)	Single 220 mm Disc
Brake Type (Rear)	Single 190 mm Disc



LIGHTWEIGHT CHASSIS



STEEL SWINGARM



37MM UP SIDE DOWN FORK (SHOWA BRAND)



PRO-LINK REAR SUSPENSION (SHOWA BRAND)



4.3 LITERS FUEL TANK CAPACITY

COLOR VARIANTS





SINGLE FRONT AND REAR DISC BRAKE



19-INCH FRONT AND 16-INCH REAR WHEELS

EXTREME RED

USE ONLY:

HONDA

GENUINE PARTS



















