







**ONE DREAM** 

## **SPECIFICATIONS**

**Engine Type** 4 Stroke Single Cylinder, Air-Cooled. Over Head Cam (OHC)

Displacement 149cc

Bore X Stroke 57.3 x 57.8 (mm)

**Maximum Power** 8.72 kW @ 8,500 rpm **Maximum Torque** 12.1 N.m @ 6,000 rpm

Starting System Electric & Kick

Transmission Type Manual, 5-Speed

**Gear Shift Pattern** 1-N-2-3-4-5

Suspension Type (Front) Telescopic Fork

Suspension Type (Rear) Swing Arm Mono-Shock

Disc Brake Type (Front) Brake Type (Rear) Drum

90/90-19 Tire Size (Front) Tire Size (Rear) 110/90-17

Wheel Type Spoke

Wheel Base 1,362 mm

Overall Dimensions: LxWxH 2.091 x 811 x 1.125 (mm)

**Curb Weight** 130 kg 825 mm Seat Height **Ground Clearance** 243 mm

**Fuel Tank Capacity** 12 L

Fuel System Carburetor **Battery Type** 12V-5Ah MF Type

Color Chart





CRF INSPIRED BODY COLOR AND GRAPHICS

Perfectly designed with the CRF look and feel giving an awesome attraction in the on/off world.



**POWERFUL 149CC ENGINE** 

Euro3 compliant 149cc engine for a more fuel efficient and environment-friendly ride. It also has Engine Balancer to reduce



FRONT SUSPENSION W/ BOOTS Durable front fork suspension with boots for protection from dirt



ROAD-READY HEAD LIGHT CRF-inspired headlight with dynamic cuts and wider design for better visibility



EASY TO READ METER PANEL Easy-to-view meter panel to make riding safer and more comfortable.



FRONT DISC BRAKE

Bigger front disc brake to give riders' high brake confidence and outstanding serviceability



LARGE CAPACITY FUEL TANK Longer rides, longer distances with high capacity fuel tank.



COMFORTABLE RIDING SEATS Ergonomically designed for on/off riding comfort even for long journeys.



REAR CARRIER Practical and useful multi-purpose grill that lets you carry light load for rider's convenience



**DURABLE MONO SHOCK** REAR SUSPENSION

On/off road performance demands a high performing shock The XR150L can take on bumps and grooves no matter what road.

Authorized Dealer

**USE ONLY:** 

HONDA

**GENUINE PARTS** 













